

Monitor Calibration Report

Date: 2011-10-7 00:11:16
Profile: C:/Windows/system32/spool/drivers/color/liyama X2775HDS sRGB Kalibrierung
06.10.11-6500K-sRGB-120cd-trc.icc
Measurement Device: DTP94-LCD mode

Calibration:

	Target	Current	Deviation
Gamma	-	-	-
Kelvin	6500	6487	0%
cd/m2	120	94	21%

Whitepoint

XYZ	89.71 94.30 102.61
XYZ (normalized):	95.14 100.00 108.81
Luminance	94.3 Cd/m2
Next Temperature	6487 Kelvin
Assumed Target Whitepoint	6500 Kelvin
Distance to assumed Target Whitepoint	0.0 deltaE

Blackpoint:

Luminance 0.00 Cd/m2

Graybalance:

Color	Kelvin	Chroma	Gamma
0% black	0	0.00	
17% heavy dark	6451	0.94	2.06
25% dark gray	6419	0.40	2.12
50% gray	6487	0.10	2.20
75% light gray	6487	0.13	2.23
100% white	6487	0.16	

Average Gamma = 2.15

Profile Statistic:

Note: The deltaE calculation takes the blackpoint into account!
Based on chromatic adaptation Bradford

Color	L	a	b	dE94
0% black	0.0	0.0	0.0	0.9
17% heavy dark	19.5	-0.7	0.6	1.1
25% dark gray	27.6	-0.1	0.4	0.5
50% gray	53.7	0.0	0.0	0.1
75% light gray	77.7	0.0	-0.0	0.0
100% white	100.0	0.0	0.0	0.0
red	50.4	74.7	67.8	0.5
green	90.6	-70.9	107.4	0.5
blue	25.9	93.0	-123.8	1.1
cyan	92.6	-38.9	-12.4	0.5
magenta	55.5	99.1	-73.1	0.2
yellow	98.6	-21.1	115.6	0.6

Average				0.5
Maximum				1.1

Metric:

	0%	50%	100%
X	0.0	19.5	89.7
Y	0.0	20.5	94.3
Z	0.0	22.3	102.6
K		6487	6487