



## SHB-22S6TW Specifications

Item	Value
Model	<b>SHB-22S6TW</b>
Panel Size	22" wide screen (16:10)
Pixel Pitch	.282mm
Surface Treatment	Anti glary
Active Area(mm <sup>2</sup> )	473.76*296.10mm
H-Frequency	30K~81KHz
V-Frequency	55~75Hz
Max Resolution	1680*1050@60Hz
Best Resolution	1680*1050@60Hz
Max Brightness (cd/m <sup>2</sup> )	300
Max Contrast	800:1
Response Time	5ms
Viewing Angle (Max.)	160°/160°
Power Consumption(Operating)	<48W
Power Consumption(Suspend)	<2W
Power Consumption(Off)	<2W
Power Supply (built-in power)	AC100~240V 60/50Hz, 1.5A
Input Resistance	Video 0.7Vp-p/75 Ohms

Control Mode	Keys, OSD
Supported Modes	640*480@60Hz,31.5KHz,25.175MHz 720*400@70Hz,31.468KHz,28.322MHz 640*480@72Hz,37.9KHz,31.5MHz 640*480@75Hz,37.5KHz,31.5MHz 800*600@60Hz,37.9KHz,40.0MHz 800*600@75Hz,46.9KHz,49.5MHz 800*600@72Hz,48.1KHz,50.0MHz 1024*768@60Hz,48.4KHz,65.0MHz 1024*768@70Hz,56.5KHz,75.0MHz 1152*864@75Hz,67.5KHz,108MHz 1280*1024@75Hz,80.0KHz,135.0MHz 1600*1200@60Hz,75.0KHz,162.0MHz 1680*1050@60Hz,64.7KHz,119.0MHz
Display Color	16.7M
Video Interface	VGA , DVI
Speaker	yes
VESA mount	optional
Operating Temperature	5~40℃
Operating Humidity	10%~85%
Storage Temperature	-20~55℃
Storage Humidity	5%~95%
Unpacked Dimension (mm <sup>3</sup> )	516 * 74 (w/o base) * 409 (L*W*H)
Packed Dimension (mm <sup>3</sup> )	580*165*465
Net Weight	6.5kg
Gross Weight	8.0kg