

UGRA

Display Analysis & Certification Tool

Report

Basics

Date: 2010-7-3 5:32:23
Report-Version: v1.3.1
Monitor-Name: \\.\DISPLAY1
Profile: C:/Windows/system32/spool/drivers/color/ugra2.icc
Created: 2010-7-3 5:28
Measurement device: eye-one pro

Summary

The monitor has passed the certification according to the UGRA DACT specifications.

Calibration

White Point	yes
Gray balance	yes
Profile quality	yes

Softproofing

MultiColor, HighBody	yes
Offset/Gravure Paper Type 1/2	yes
Offset on uncoated paper	yes
Newspaper Printing	yes
sRGB	yes
AdobeRGB	yes
ECI-RGB	yes

Diagram



Whitepoint

The whitepoint should be as close as possible to the black body curve and the calibration target. The maximum allowed distance to the target whitepoint is DeltaE 2.0.

XYZ:	133.86 140.55 137.21
XYZ (normalized):	95.24 100.00 97.62
Luminance:	140.5 Cd/m2
Next Temperature:	5824 Kelvin
Assumed Target Whitepoint:	5800 Kelvin
Distance to assumed Target Whitepoint:	0.3 deltaE

Blackpoint

The blackpoint is not defined in ISO 12646. Therefore UDACT does only measure but not assess it.

Luminance:	0.4 Cd/m2
Chromaticity:	0.2 Chroma (Lab)

Gray balance

Average and maximum calculation will respect measurements with 1% minimum luminance only. The maximum allowed deviations to comply with this test are an average of DeltaC 1.0 and a range of DeltaC 2.0.

%	Kelvin	Cd/m2	L	Chroma	Gamma
0	5567	0.45	2.88	0.20	
5	5653	0.89	5.73	0.63	1.93
10	5829	2.30	13.46	0.37	1.88
15	5792	4.52	20.88	0.29	1.87
20	5832	7.59	27.85	0.63	1.85
25	5774	10.95	33.55	0.82	1.88
30	5815	15.47	39.59	0.76	1.86
35	5796	20.67	45.23	0.67	1.85
40	5800	26.44	50.47	0.63	1.84
45	5790	32.24	55.01	0.53	1.86
50	5821	39.42	59.93	0.63	1.85
55	5812	47.01	64.52	0.60	1.85
60	5788	55.21	68.96	0.53	1.85
65	5794	63.39	72.96	0.29	1.86
70	5788	72.77	77.15	0.41	1.86
75	5773	82.86	81.27	0.48	1.85
80	5778	93.28	85.18	0.44	1.85
85	5783	103.98	88.92	0.40	1.87
90	5790	115.71	92.72	0.33	1.86
95	5790	127.83	96.39	0.37	1.86
100	5824	140.55	100.00	0.00	
Average	5798			0.48	1.86
Range				0.96	
Max				0.82	

Tone values = 100.0%

Through the calibration of a display tone values can be lost. A display for the printing industry should show at least 95% of the incoming tone values.

Profile Quality

This test displays and measures RGB values and compares them with the transformation of the profile. The maximum allowed deviations to comply with this test are an average of DeltaE 3.0 and a maximum of DeltaE 6.0.

The assumed chromatic adaptation is: CAT02

RGB	Lab	deltaLab	deltaE
0 0 0	2.9 0.1 0.2	-2.9 -0.1 -0.2	2.9
0 0 128	13.1 47.6 -74.9	-0.4 2.9 -2.4	3.7
0 0 255	26.7 77.2 -118.1	0.7 -0.9 1.1	1.6
0 128 0	50.8 -85.6 52.2	0.4 -2.9 0.7	3.0
0 128 128	52.6 -58.8 -12.1	0.3 -0.5 -0.9	1.0
0 170 255	67.3 -43.8 -51.9	0.4 -0.2 0.8	0.9
0 255 0	85.8 -133.0 81.7	-0.2 -0.8 -1.7	1.9
0 255 170	86.9 -110.9 16.9	-0.1 0.6 -1.7	1.8
0 255 255	88.2 -90.2 -19.5	-0.1 0.5 -0.2	0.6
85 85 85	43.5 -0.5 0.5	0.5 0.5 -0.5	0.9
128 0 0	33.7 65.8 49.1	0.3 2.0 4.1	4.6
128 0 128	36.4 74.0 -35.8	0.5 1.5 -0.2	1.6
128 128 0	58.8 -10.9 64.3	0.6 -0.2 0.5	0.8
128 128 128	60.3 -0.6 0.3	0.4 0.6 -0.3	0.8
128 128 255	63.3 21.7 -57.7	0.5 0.3 1.2	1.3
128 255 128	90.2 -75.6 41.5	-0.1 1.0 -1.5	1.8
170 0 255	49.5 97.8 -79.4	0.7 -0.1 1.4	1.6
170 170 170	74.6 -0.1 0.3	0.4 0.0 -0.3	0.5
170 255 0	91.9 -61.2 91.2	-0.1 0.3 -2.0	2.0
170 255 255	94.1 -37.0 -9.7	0.0 0.5 0.1	0.5
255 0 0	59.7 102.2 84.7	-0.0 0.4 0.0	0.4
255 0 170	61.6 108.4 -17.1	0.2 0.0 -0.4	0.4
255 0 255	63.7 114.6 -55.5	0.4 -0.5 1.0	1.2
255 128 128	75.0 59.0 24.3	0.2 -0.5 -0.6	0.8
255 170 0	81.5 31.2 90.3	0.3 -1.2 -1.4	1.9
255 170 255	84.3 46.8 -23.5	0.3 -0.6 0.7	1.0
255 255 0	98.0 -16.4 100.3	-0.1 -0.4 -2.3	2.3
255 255 170	99.0 -8.5 36.1	-0.0 0.1 -1.2	1.2
255 255 255	100.0 0.0 0.0	0.0 -0.0 0.0	0.0
170 85 85	55.1 46.0 19.4	0.4 -0.0 -0.7	0.8
85 170 85	66.8 -59.1 32.6	0.4 0.3 -1.1	1.2
85 85 170	45.8 16.9 -44.6	0.6 0.4 0.2	0.8
85 170 170	68.1 -43.5 -10.3	0.4 0.6 -0.4	0.8
170 85 170	56.7 54.3 -26.5	0.5 -0.0 0.0	0.5
170 170 85	73.5 -8.9 43.1	0.3 -0.3 -1.0	1.1
Average			1.4
Maximum			4.6

Gamut-Volume

These measurements are only informative.

Gamut-Volume	
ISO	100 %
sRGB	100 %
AdobeRGB	99 %
ECI-RGB v1.0	92 %

ISO-Gamut

This test displays and measures Lab values and compares them with the reference. The maximum allowed deviations to comply with this test are an average of DeltaE 4.0 and a minimum Gamut volume of 90% for ISOcoated.

Reference	Lab	deltaLab
55.0 -37.0 -50.0	55.3 -33.0 -48.8	4.2
66.9 -24.7 -37.1	66.4 -25.1 -37.4	0.6
79.7 -12.5 -21.8	79.4 -12.7 -21.9	0.4
48.0 74.0 -3.0	47.6 73.7 -2.6	0.7
60.8 50.6 -6.7	60.3 50.8 -6.4	0.6
76.4 25.8 -6.9	76.1 26.2 -6.6	0.7
89.0 -5.0 93.0	88.8 -3.5 92.9	1.5
90.3 -4.7 62.6	90.3 -3.9 64.0	1.6
92.2 -3.5 31.1	92.1 -3.3 32.2	1.0
53.1 37.7 28.9	52.7 37.8 30.0	1.2
41.5 22.7 16.8	41.2 22.8 17.2	0.6
31.9 40.0 24.0	31.6 39.5 23.4	0.8
32.5 44.5 -1.8	32.0 43.7 -1.4	1.0
51.3 1.3 44.5	50.8 2.0 44.8	0.9
34.6 -36.4 13.9	34.1 -34.8 13.9	1.7
36.0 -26.2 -20.9	35.5 -25.9 -20.5	0.7
20.9 9.6 -23.6	20.9 7.9 -22.2	2.3
89.0 0.0 -1.9	88.8 0.1 -1.6	0.3
82.8 0.0 -1.7	82.4 0.1 -1.6	0.4
69.3 0.0 -1.4	68.9 -0.4 -0.8	0.8
54.1 0.0 -1.0	53.6 -0.0 -0.5	0.7
36.6 0.0 -0.5	36.0 -0.2 0.0	0.9
16.0 0.0 0.0	16.5 -0.2 0.4	0.7
24.0 22.0 -46.0	23.9 21.5 -45.2	1.0
40.9 17.9 -36.6	40.1 17.9 -36.6	0.8
63.7 10.3 -23.8	63.2 10.0 -23.6	0.6
47.0 68.0 48.0	46.5 67.9 48.2	0.6
58.5 47.1 37.9	58.1 47.7 38.8	1.1
74.2 22.9 21.4	74.0 23.6 22.0	0.9
50.0 -65.0 27.0	49.6 -64.3 27.8	1.1
62.1 -39.8 21.0	61.6 -39.8 21.9	1.1
77.0 -19.1 11.0	76.7 -19.3 11.6	0.7
71.2 18.9 17.3	70.8 19.1 17.7	0.7
71.2 22.1 73.1	71.0 23.1 74.4	1.7
47.7 71.2 16.2	47.3 70.9 16.8	0.8
38.0 55.4 -20.9	37.6 54.6 -20.2	1.1
73.7 -22.8 67.6	73.3 -22.8 68.9	1.3
52.3 -52.3 -20.1	51.9 -52.3 -19.4	0.8
43.3 -17.0 -48.6	42.7 -17.1 -48.4	0.7
95.0 0.0 -2.0	94.9 0.4 -2.1	0.4
88.5 -0.4 -3.1	88.4 -0.6 -2.7	0.5
82.0 -0.9 -4.1	81.6 -0.9 -3.7	0.5
67.7 -2.0 -4.4	67.1 -2.3 -4.1	0.7
52.2 -2.5 -3.5	51.9 -3.5 -2.7	1.4
37.5 -3.9 -3.1	37.0 -4.7 -2.7	1.1
26.3 -6.8 -3.4	26.2 -7.0 -3.0	0.5
Average		1.0
Gamut-Volume		100 %

Measurement Data

This table lists all RGB measurements. The XYZ values represent the values from the measurement device.

RGB	XYZ	RGB	XYZ
255 255 255	133.86 140.55 137.21	85 85 170	25.59 21.74 59.24
0 0 0	0.43 0.45 0.42	85 170 170	35.35 53.93 64.15
12 12 12	0.84 0.89 0.82	170 85 170	53.77 34.61 59.93
25 25 25	2.18 2.30 2.22	170 170 85	56.01 64.00 23.70
38 38 38	4.29 4.52 4.36	0 130 208	23.95 33.41 86.62
51 51 51	7.17 7.59 7.31	84 159 221	40.26 51.15 98.92
63 63 63	10.36 10.95 10.45	154 193 232	69.00 78.72 111.01
76 76 76	14.62 15.47 14.86	171 39 103	44.80 22.85 24.24
89 89 89	19.59 20.67 19.88	185 96 143	58.60 39.84 45.09
102 102 102	25.08 26.44 25.49	206 159 190	81.29 70.27 77.52
114 114 114	30.63 32.24 31.12	237 216 0	93.63 102.60 11.92
127 127 127	37.38 39.42 38.13	237 221 87	97.85 107.10 29.34
140 140 140	44.61 47.01 45.47	236 228 158	104.60 113.22 63.10
153 153 153	52.50 55.21 53.36	156 85 63	39.12 28.76 11.91
165 165 165	60.38 63.39 61.54	106 68 56	20.59 16.65 9.25
178 178 178	69.29 72.77 70.50	97 37 31	15.40 9.54 3.48
191 191 191	78.99 82.86 80.23	98 36 64	16.81 9.88 10.23
204 204 204	88.93 93.28 90.42	116 101 33	25.42 26.57 6.04
216 216 216	99.14 103.98 100.89	35 74 44	6.27 11.32 6.53
229 229 229	110.35 115.71 112.50	26 76 98	8.45 12.47 22.34
242 242 242	121.99 127.83 124.44	36 36 67	5.16 4.58 10.78
0 0 128	6.53 2.58 33.52	215 216 220	98.95 103.75 103.99
0 0 255	22.64 8.31 120.48	194 195 199	81.86 85.85 86.18
0 128 0	8.35 26.74 4.33	152 153 155	52.27 55.03 54.55
0 128 128	14.68 29.33 37.94	110 110 112	28.94 30.38 30.05
0 170 255	36.26 53.26 127.88	68 68 69	12.00 12.64 12.32
0 255 0	28.83 94.79 14.37	30 30 30	2.92 3.08 2.95
0 255 170	39.37 98.69 71.06	39 37 108	8.37 5.95 25.33
0 255 255	51.30 103.00 135.33	78 71 138	19.55 16.19 40.62
85 85 85	17.95 18.98 18.24	137 132 183	47.25 44.99 70.33
128 0 0	23.07 10.76 0.84	169 42 29	40.22 21.44 3.69
128 0 128	29.38 13.02 34.39	185 91 62	52.01 36.10 12.18
128 128 0	31.33 37.27 4.74	206 153 127	73.62 65.08 40.57
128 128 128	37.82 39.92 38.72	35 120 54	10.87 25.43 10.69
128 128 255	54.02 45.87 125.78	93 148 92	27.01 42.02 24.05
128 255 128	58.50 107.78 48.86	156 186 153	58.47 71.60 55.84
170 0 255	61.45 26.03 121.67	189 147 126	64.42 58.54 39.45
170 170 170	63.67 66.89 64.91	205 144 23	65.83 58.50 7.59
170 255 0	68.03 112.53 14.96	171 41 73	42.86 22.38 13.54
170 255 255	90.75 120.92 136.33	117 39 105	25.11 13.80 24.44
255 0 0	82.37 37.86 1.81	158 176 33	49.25 63.56 10.73
255 0 170	92.92 41.57 58.91	10 125 140	15.59 28.62 43.63
255 0 255	104.63 45.69 122.76	16 92 167	15.39 18.77 57.33
255 128 128	96.97 66.94 40.04	236 237 242	117.44 122.90 123.93
255 170 0	96.01 82.30 8.37	212 215 221	97.34 102.49 104.49
255 170 255	118.74 90.97 129.83	189 193 201	79.53 83.91 87.29
255 255 0	111.31 132.22 15.72	143 149 156	48.42 51.73 54.90
255 255 170	121.89 136.18 73.28	101 107 111	25.94 28.20 29.40
170 85 85	46.21 31.92 18.85	65 72 75	12.08 13.47 14.30
85 170 85	27.65 51.04 23.01	41 50 52	5.78 6.80 7.46