

Colorimetric Report

Page (1/1)



CCalc 2.1
Copyright © 2015, Denis Freund
All Rights Reserved
licensed for PRAD ProAdviser

Date	Thursday, April 7, 2016
Display	Fujitsu B24-8 TE Pro
Sensor	X-Rite i1 Display Pro (EDR: WLED)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6896 Kelvin
White Point XYZ (normalized)	97.06 100.00 118.18
DeltaE to D50/ D65	25.46/ 6.55
Assumed Target Whitepoint (1)	6900 Kelvin
DeltaE to Assumed Target Whitepoint	4.23
Brightness	183.83 cd/m ²
Black Point	0.17 cd/m ²
Contrast (x:1)	1081:1
Gradation (Average)	2.14

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	7017	0.20	-	2.17
	15	6649	1.04	-	2.23
	20	6460	1.82	-	2.24
	25	6380	2.47	-	2.21
	30	6405	2.99	-	2.20
	35	6323	3.26	-	2.18
	40	6339	3.80	-	2.16
	45	6341	4.27	-	2.15
	50	6314	4.95	-	2.15
	55	6343	4.77	-	2.13
	60	6343	5.14	-	2.11
	65	6362	5.65	-	2.13
	70	6356	5.78	-	2.16
	75	6372	6.01	-	2.20
	80	6424	5.30	-	2.20
	85	6453	5.30	-	2.12
	90	6499	5.12	-	1.98
	95	6514	5.70	-	1.84
	100 (2)	6896	-	-	-
	Average (3)	-	4.32	-	2.14
	Maximum (3)	-	6.01	-	-
	Range (3)	-	6.01	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

