

Colorimetric Report

Page (1/1)



CCalc 2.2
Copyright © 2015, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Tuesday, February 28, 2017
Tester	
Display	Eizo FlexScan EV2456-BK
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6591 Kelvin
White Point XYZ (normalized)	94.28 100.00 108.89
DeltaE to D50/ D65	19.72/ 1.35
Assumed Target Whitepoint (1)	6600 Kelvin
DeltaE to Assumed Target Whitepoint	1.50
Brightness	189.74 cd/m²
Black Point	0.23 cd/m²
Contrast (x:1)	825:1
Gradation (Average)	2.22

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	7384	1.57	-	2.13
	15	6825	0.85	-	2.17
	20	6584	0.34	-	2.19
	25	6538	0.20	-	2.19
	30	6595	0.27	-	2.20
	35	6482	0.46	-	2.20
	40	6469	0.51	-	2.20
	45	6468	0.58	-	2.21
	50	6424	0.84	-	2.21
	55	6447	0.84	-	2.22
	60	6484	0.60	-	2.22
	65	6475	0.69	-	2.22
	70	6476	0.77	-	2.23
	75	6489	0.78	-	2.23
	80	6506	0.61	-	2.23
	85	6513	0.75	-	2.26
	90	6538	0.58	-	2.29
	95	6549	0.48	-	2.33
	100 (2)	6591	-	-	-
	Average (3)	-	0.6	-	2.22
	Maximum (3)	-	0.85	-	-
	Range (3)	-	1.62	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

