

Colorimetric Report

Page (1/1)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Tuesday, March 26, 2019
Tester	Denis Freund
Display	Eizo EV2457
Sensor	X-Rite i1 Pro
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6410 Kelvin
White Point XYZ (normalized)	94.59 100.00 106.61
DeltaE to D50/ D65	18.11/ 1.62
Assumed Target Whitepoint (1)	6400 Kelvin
DeltaE to Assumed Target Whitepoint	0.89
Brightness (2)	145.50 cd/m²
Black Point (2)	0.14 cd/m²
Contrast (x:1)	1039:1
Gradation (Average)	2.17

(1) Daylight (2) Measured separately

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6872	0.77	-	2.20
	15	6425	0.45	-	2.24
	20	6277	0.54	-	2.25
	25	6216	0.60	-	2.25
	30	6210	0.71	-	2.24
	35	6207	0.81	-	2.24
	40	6225	0.84	-	2.23
	45	6246	0.83	-	2.21
	50	6272	0.79	-	2.20
	55	6262	0.87	-	2.19
	60	6298	0.76	-	2.18
	65	6287	0.87	-	2.16
	70	6308	0.70	-	2.14
	75	6349	0.55	-	2.12
	80	6356	0.47	-	2.09
	85	6368	0.36	-	2.07
	90	6380	0.27	-	2.05
	95	6407	0.10	-	2.05
	100 (3)	6411	-	-	-
	Average (4)	-	0.62	-	2.17
	Maximum (4)	-	0.87	-	-
	Range (4)	-	1.15	-	-

(3) Visual adaptation to display whitepoint is assumed
(4) Only luminance > 1% considered

Corresponding Gamma

