

Colorimetric Report

Page (1/5)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, July 24, 2020
Tester	Manuel Findeis
Display	BenQ BL2483TM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

White Point (CCT)	6617 Kelvin
White Point XYZ (normalized)	96.33 100.00 112.91
DeltaE to D50/ D65	22.03/ 3.31
Assumed Target Whitepoint (2)	6600 Kelvin
DeltaE to Assumed Target Whitepoint	2.83
Brightness	309.24 cd/m²
Black Point	0.28 cd/m²
Contrast (x:1)	1104:1
Gradation (Average)	2.67


(2) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	8622	1.69	4.56	2.27
	15	8016	2.01	5.66	2.36
	20	7251	1.69	5.66	2.41
	25	7455	1.97	6.31	2.47
	30	7338	2.34	6.51	2.51
	35	7153	2.17	6.39	2.53
	40	7101	2.19	6.44	2.56
	45	7041	2.56	6.27	2.57
	50	6970	2.74	6.37	2.60
	55	6943	2.77	6.27	2.63
	60	6957	2.73	6.19	2.67
	65	6879	2.92	6.05	2.70
	70	6790	3.06	5.86	2.74
	75	6762	2.91	5.70	2.82
	80	6732	3.49	5.44	2.85
	85	6610	3.52	5.11	2.95
	90	6598	3.41	4.55	3.10
	95	6517	3.23	3.88	3.39
	100 (3)	6618	-	-	-
	Average (4)	-	2.69	5.8	2.67
	Maximum (4)	-	3.52	6.51	-
	Range (4)	-	4.42	-	-

(3) Visual adaptation to display whitepoint is assumed

(4) Only luminance > 1% considered

Corresponding Gamma



Colorimetric Report

Page (2/5)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, July 24, 2020
Tester	Manuel Findeis
Display	BenQ BL2483TM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	0 0 0	1.09	0.00	0.81	1.35
	0 0 63	7.95	0.38	1.01	2.88
	0 0 127	3.08	6.75	4.81	5.75
	0 0 191	8.60	9.34	5.80	6.97
	0 0 255	15.81	8.57	2.41	4.36
	0 63 0	6.29	3.20	5.42	6.13
	0 63 63	2.89	2.14	5.87	6.30
	0 63 127	4.84	8.03	6.64	8.44
	0 63 191	11.60	11.02	7.10	9.07
	0 63 255	20.79	11.56	4.33	6.99
	0 127 0	1.22	1.20	5.32	5.36
	0 127 63	1.23	1.79	5.52	5.63
	0 127 127	2.37	0.51	5.98	6.08
	0 127 191	2.50	8.15	6.48	8.23
	0 127 255	17.24	13.25	5.16	9.05
	0 191 0	5.65	4.26	4.87	5.28
	0 191 63	5.14	4.32	4.97	5.43
	0 191 127	1.63	3.22	5.26	5.55
	0 191 191	2.90	0.93	5.63	5.75
	0 191 255	6.88	14.66	4.97	10.24
	0 255 0	15.36	13.37	0.71	5.40
	0 255 63	14.34	13.26	0.62	5.56
	0 255 127	9.96	11.70	0.38	5.36
	0 255 191	4.04	9.80	0.06	5.00
	0 255 255	4.20	1.14	0.25	1.47
	63 0 0	10.21	3.80	2.95	5.66
	63 0 63	4.55	1.22	3.93	4.29
	63 0 127	1.37	2.47	5.42	5.55
	63 0 191	7.51	6.27	6.24	6.83
	63 0 255	15.82	6.45	3.04	4.38
	63 63 0	6.16	4.51	5.72	6.86
	63 63 63	1.75	0.20	6.02	6.27
	63 63 127	4.10	2.92	6.71	7.10
	63 63 191	10.24	7.27	7.18	8.24
	63 63 255	20.04	8.82	4.61	6.57
	63 127 0	3.61	2.29	5.00	5.22
	63 127 63	4.52	0.51	5.15	5.37
	63 127 127	1.04	1.09	5.60	5.69
	63 127 191	2.50	4.45	6.10	6.77
	63 127 255	15.98	9.74	4.87	7.69
	63 191 0	8.04	1.87	4.28	4.62
	63 191 63	7.86	2.51	4.37	4.83
	63 191 127	4.80	2.63	4.65	5.06
	63 191 191	0.39	0.82	5.02	5.05
	63 191 255	7.17	11.27	4.41	8.46
	63 255 0	16.55	11.25	0.49	4.89
	63 255 63	15.64	11.26	0.42	5.08

Colorimetric Report

Page (3/5)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, July 24, 2020
Tester	Manuel Findeis
Display	BenQ BL2483TM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	63 255 127	11.47	10.15	0.19	4.99
	63 255 191	5.55	8.85	0.13	4.76
	63 255 255	2.94	1.07	0.06	1.14
	127 0 0	12.40	3.24	4.06	5.51
	127 0 63	6.69	0.56	4.11	4.60
	127 0 127	3.02	0.53	5.03	5.09
	127 0 191	3.27	1.57	5.87	5.93
	127 0 255	14.07	1.77	3.61	4.24
	127 63 0	8.98	0.20	5.82	6.43
	127 63 63	3.36	0.44	5.81	5.99
	127 63 127	1.39	1.17	6.36	6.41
	127 63 191	7.33	1.96	6.85	7.10
	127 63 255	17.80	3.35	4.83	5.84
	127 127 0	1.18	6.30	5.33	6.32
	127 127 63	3.17	4.61	5.34	6.24
	127 127 127	3.19	0.34	5.72	6.56
	127 127 191	2.89	0.59	6.13	6.24
	127 127 255	15.45	4.18	5.02	6.52
	127 191 0	8.62	2.62	4.50	4.99
	127 191 63	8.90	1.34	4.50	5.04
	127 191 127	6.58	0.01	4.76	5.27
	127 191 191	1.81	1.23	5.10	5.26
	127 191 255	9.45	6.72	4.50	7.12
	127 255 0	18.55	6.13	0.07	3.90
	127 255 63	17.75	6.73	0.04	4.20
	127 255 127	13.94	6.55	0.17	4.31
	127 255 191	8.26	6.68	0.46	4.45
	127 255 255	0.40	0.86	0.24	0.62
	191 0 0	12.21	2.17	3.91	4.77
	191 0 63	6.57	3.00	3.69	4.28
	191 0 127	5.50	1.18	4.26	4.48
	191 0 191	0.83	0.10	4.98	4.98
	191 0 255	10.61	2.80	3.57	4.07
	191 63 0	8.71	1.45	5.25	5.65
	191 63 63	3.80	0.97	5.03	5.16
	191 63 127	1.74	0.58	5.43	5.46
	191 63 191	3.20	0.86	5.91	5.96
	191 63 255	14.02	2.11	4.55	5.22
	191 127 0	2.88	5.47	5.24	5.96
	191 127 63	0.55	5.02	5.11	5.89
	191 127 127	2.83	1.99	5.39	5.72
	191 127 191	1.07	1.45	5.77	5.85
	191 127 255	13.33	1.66	4.84	5.81
	191 191 0	6.44	6.05	4.59	5.56
	191 191 63	7.30	4.79	4.50	5.46
	191 191 127	5.52	3.88	4.70	5.79
	191 191 191	2.97	0.37	4.99	5.82

Colorimetric Report

Page (4/5)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, July 24, 2020
Tester	Manuel Findeis
Display	BenQ BL2483TM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	191 191 255	10.26	0.20	4.43	6.00
	191 255 0	19.27	0.11	0.36	3.50
	191 255 63	18.80	0.95	0.32	3.73
	191 255 127	15.48	1.41	0.50	3.92
	191 255 191	10.78	2.87	0.76	4.31
	191 255 255	1.93	0.60	0.53	1.22
	255 0 0	1.77	4.36	0.59	1.83
	255 0 63	0.09	8.50	0.81	3.68
	255 0 127	2.44	8.47	1.35	4.00
	255 0 191	2.80	5.37	2.08	3.08
	255 0 255	6.01	2.34	1.50	1.98
	255 63 0	0.97	2.71	1.74	2.07
	255 63 63	2.46	5.64	1.94	3.20
	255 63 127	0.51	5.69	2.37	3.58
	255 63 191	0.75	3.48	2.97	3.34
	255 63 255	9.00	2.50	2.36	2.99
	255 127 0	4.22	3.00	2.44	2.90
	255 127 63	5.12	4.60	2.57	3.61
	255 127 127	2.55	5.12	2.91	4.13
	255 127 191	1.16	3.02	3.36	3.75
	255 127 255	9.30	2.60	2.84	3.71
	255 191 0	8.97	2.56	2.49	3.32
	255 191 63	9.44	3.11	2.57	3.74
	255 191 127	6.82	3.82	2.83	4.30
	255 191 191	1.82	3.90	3.16	4.34
	255 191 255	7.31	2.38	2.80	4.10
	255 255 0	19.59	0.20	0.34	3.67
	255 255 63	19.21	0.23	0.26	3.92
	255 255 127	15.71	0.45	0.06	4.12
	255 255 191	11.01	0.31	0.21	4.51
	255 255 255 (1)	-	-	-	-
	Average (2)	7.27	3.97	3.65	5.12
	Maximum (2)	20.79	14.66	7.18	10.24

(1) Visual adaptation to display whitepoint is assumed; CIELAB reference values are adapted (Bradford transformation) to display whitepoint
(2) Without Black

Color Space	Gamut Volume CIELAB D50
sRGB	93%

Colorimetric Report

Page (5/5)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, July 24, 2020
Tester	Manuel Findeis
Display	BenQ BL2483TM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

Property	Device adjustments
Backlight brightness	
Brightness	
Contrast	
RGB Gain	
Gradation	
Other	