

Colorimetric Report

Page (1/1)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Monday, November 2, 2020
Tester	Manuel Findeis
Display	EIZO EV2495
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6773 Kelvin
White Point XYZ (normalized)	94.12 100.00 111.35
DeltaE to D50/ D65	21.39/ 2.22
Assumed Target Whitepoint (1)	6800 Kelvin
DeltaE to Assumed Target Whitepoint	1.82
Brightness	220.03 cd/m²
Black Point	0.22 cd/m²
Contrast (x:1)	1000:1
Gradation (Average)	2.18

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	7301	0.91	-	2.11
	15	7085	0.67	-	2.12
	20	6987	0.52	-	2.13
	25	6949	0.49	-	2.13
	30	6917	0.46	-	2.13
	35	6904	0.47	-	2.14
	40	6873	0.41	-	2.14
	45	6814	0.27	-	2.15
	50	6787	0.11	-	2.16
	55	6793	0.25	-	2.17
	60	6782	0.36	-	2.18
	65	6746	0.21	-	2.20
	70	6752	0.41	-	2.21
	75	6740	0.35	-	2.23
	80	6740	0.45	-	2.25
	85	6743	0.41	-	2.27
	90	6741	0.45	-	2.29
	95	6754	0.34	-	2.29
	100 (2)	6774	-	-	-
	Average (3)	-	0.39	-	2.18
	Maximum (3)	-	0.67	-	-
	Range (3)	-	1.09	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

