

Colorimetric Report

Page (1/1)



CCalc 2.5
Copyright © 2020, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, May 6, 2021
Tester	Manuel Findeis
Display	EIZO EV2480
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6665 Kelvin
White Point XYZ (normalized)	95.27 100.00 111.75
DeltaE to D50/ D65	21.36/ 1.78
Assumed Target Whitepoint (1)	6700 Kelvin
DeltaE to Assumed Target Whitepoint	0.52
Brightness	193.07 cd/m²
Black Point	0.18 cd/m²
Contrast (x:1)	1073:1
Gradation (Average)	2.19

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	7366	1.67	-	2.14
	15	7002	1.12	-	2.17
	20	6881	0.79	-	2.19
	25	6821	0.63	-	2.20
	30	6802	0.44	-	2.20
	35	6720	0.50	-	2.20
	40	6693	0.53	-	2.20
	45	6668	0.12	-	2.20
	50	6672	0.09	-	2.20
	55	6665	0.33	-	2.19
	60	6680	0.37	-	2.19
	65	6684	0.33	-	2.19
	70	6657	0.36	-	2.18
	75	6675	0.45	-	2.19
	80	6656	0.31	-	2.19
	85	6672	0.38	-	2.20
	90	6667	0.49	-	2.22
	95	6661	0.50	-	2.23
	100 (2)	6665	-	-	-
	Average (3)	-	0.46	-	2.19
	Maximum (3)	-	1.12	-	-
	Range (3)	-	1.12	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

