

Colorimetric Report

Page (1/1)



CCalc 2.4
Copyright © 2018, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, April 2, 2022
Tester	
Display	AOpen_43XV1CP
Sensor	X-Rite i1 Pro
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6525 Kelvin
White Point XYZ (normalized)	95.99 100.00 110.92
DeltaE to D50/ D65	20.74/ 2.06
Assumed Target Whitepoint (1)	6500 Kelvin
DeltaE to Assumed Target Whitepoint	2.15
Brightness (2)	292.50 cd/m²
Black Point (2)	0.29 cd/m²
Contrast (x:1)	1009:1
Gradation (Average)	2.40

(1) Daylight (2) Measured separately

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6862	0.47	-	2.29
	15	6588	0.19	-	2.35
	20	6404	0.29	-	2.37
	25	6351	0.51	-	2.35
	30	6343	0.66	-	2.35
	35	6347	0.77	-	2.36
	40	6343	0.92	-	2.36
	45	6329	1.02	-	2.36
	50	6330	1.13	-	2.37
	55	6340	1.19	-	2.36
	60	6342	1.26	-	2.37
	65	6347	1.32	-	2.38
	70	6352	1.35	-	2.40
	75	6358	1.38	-	2.41
	80	6366	1.41	-	2.43
	85	6375	1.41	-	2.47
	90	6387	1.36	-	2.55
	95	6409	1.19	-	2.75
	100 (3)	6525	-	-	-
	Average (4)	-	1.02	-	2.4
	Maximum (4)	-	1.41	-	-
	Range (4)	-	1.6	-	-

(3) Visual adaptation to display whitepoint is assumed

(4) Only luminance > 1% considered

Corresponding Gamma

