

Colorimetric Report

Page (1/1)



CCalc 2.5
Copyright © 2020, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Monday, July 18, 2022
Tester	Manuel Findeis
Display	Fujitsu P2410 TS CAM
Sensor	X-Rite i1 Display Pro (Corr.: WLED, XR)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6305 Kelvin
White Point XYZ (normalized)	94.63 100.00 104.97
DeltaE to D50/ D65	16.99/ 2.53
Assumed Target Whitepoint (1)	6300 Kelvin
DeltaE to Assumed Target Whitepoint	0.91
Brightness	227.60 cd/m²
Black Point	0.21 cd/m²
Contrast (x:1)	1084:1
Gradation (Average)	2.17

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6541	0.71	-	1.96
	15	6453	0.55	-	2.04
	20	6398	0.45	-	2.09
	25	6378	0.38	-	2.13
	30	6316	0.67	-	2.15
	35	6321	0.49	-	2.17
	40	6343	0.29	-	2.18
	45	6333	0.17	-	2.19
	50	6328	0.14	-	2.20
	55	6305	0.07	-	2.20
	60	6315	0.07	-	2.20
	65	6320	0.15	-	2.21
	70	6322	0.13	-	2.21
	75	6318	0.18	-	2.21
	80	6320	0.13	-	2.21
	85	6317	0.13	-	2.21
	90	6323	0.17	-	2.20
	95	6310	0.09	-	2.21
	100 (2)	6305	-	-	-
	Average (3)	-	0.28	-	2.17
	Maximum (3)	-	0.71	-	-
	Range (3)	-	0.75	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

