

Colorimetric Report

Page (1/5)



CCalc 2.6
Copyright © 2023, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, October 12, 2023
Tester	Simon Blohm
Display	ASUS VA34VCPSN
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

White Point (CCT)	6477 Kelvin
White Point XYZ (normalized)	95.91 100.00 110.04
DeltaE to D50/ D65	20.16/ 1.67
Assumed Target Whitepoint (2)	6500 Kelvin
DeltaE to Assumed Target Whitepoint	1.75
Brightness (3)	0.00 cd/m²
Black Point (3)	0.20 cd/m²
Contrast (x:1)	-
Gradation (Average)	2.17


(2) Daylight (3) Measured separately

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6973	0.79	1.99	2.10
	15	7274	1.52	1.99	2.14
	20	7038	1.33	1.46	2.15
	25	6938	1.33	1.36	2.16
	30	6919	1.42	1.42	2.17
	35	6784	1.12	1.17	2.17
	40	6787	1.27	1.34	2.18
	45	6704	1.00	1.17	2.18
	50	6704	1.07	1.28	2.18
	55	6643	0.84	1.12	2.18
	60	6627	0.85	1.26	2.17
	65	6630	0.96	1.32	2.17
	70	6604	0.80	1.17	2.17
	75	6577	0.65	1.02	2.17
	80	6573	0.65	0.91	2.17
	85	6533	0.41	0.63	2.18
	90	6525	0.38	0.51	2.18
	95	6508	0.28	0.33	2.18
	100 (4)	6476	-	-	-
	Average (5)	-	0.93	1.15	2.17
	Maximum (5)	-	1.52	1.99	-
	Range (5)	-	1.52	-	-

(4) Visual adaptation to display whitepoint is assumed

(5) Only luminance > 1% considered

Corresponding Gamma



Colorimetric Report

Page (2/5)



CCalc 2.6
Copyright © 2023, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, October 12, 2023
Tester	Simon Blohm
Display	ASUS VA34VCPSN
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	0 0 0	0.77	0.00	0.42	0.88
	0 0 63	2.47	0.03	0.11	0.84
	0 0 127	0.47	1.35	0.44	0.76
	0 0 191	1.23	1.56	0.26	0.68
	0 0 255	0.16	0.77	0.14	0.29
	0 63 0	2.34	5.26	2.19	3.95
	0 63 63	3.70	0.11	1.26	2.38
	0 63 127	2.09	0.06	0.89	1.15
	0 63 191	2.40	0.81	0.55	0.84
	0 63 255	0.65	0.22	0.07	0.15
	0 127 0	9.94	6.59	1.42	4.21
	0 127 63	10.46	4.54	0.66	4.07
	0 127 127	7.59	1.23	0.52	3.39
	0 127 191	1.97	4.50	0.30	2.86
	0 127 255	0.91	4.02	0.06	1.92
	0 191 0	14.85	7.69	1.16	4.36
	0 191 63	14.71	7.17	0.63	4.48
	0 191 127	12.67	4.32	0.53	4.17
	0 191 191	10.58	2.04	0.36	3.99
	0 191 255	4.16	7.93	0.17	4.88
	0 255 0	19.08	8.02	1.49	4.40
	0 255 63	17.82	8.20	1.19	4.45
	0 255 127	15.35	7.47	1.13	4.54
	0 255 191	13.89	3.91	1.04	4.11
	0 255 255	12.33	2.77	0.88	4.20
	63 0 0	0.59	3.19	1.05	2.39
	63 0 63	2.54	0.98	0.64	1.24
	63 0 127	3.32	1.68	0.41	1.18
	63 0 191	2.95	1.89	0.18	0.92
	63 0 255	1.11	1.34	0.17	0.51
	63 63 0	0.76	1.32	1.37	1.64
	63 63 63	1.36	0.17	0.33	1.41
	63 63 127	2.64	0.33	0.03	0.95
	63 63 191	2.53	0.93	0.22	0.74
	63 63 255	0.41	0.40	0.50	0.53
	63 127 0	7.99	5.68	0.68	3.59
	63 127 63	7.26	4.74	0.13	3.72
	63 127 127	6.08	0.52	0.36	3.15
	63 127 191	1.13	4.06	0.56	2.64
	63 127 255	1.55	3.73	0.80	1.98
	63 191 0	14.00	7.37	0.62	4.17
	63 191 63	12.40	7.08	0.03	4.23
	63 191 127	10.78	4.91	0.07	4.13
	63 191 191	9.44	1.56	0.22	3.78
	63 191 255	3.19	7.72	0.41	4.80
	63 255 0	18.05	7.43	1.20	4.13
	63 255 63	15.87	8.09	0.90	4.21

Colorimetric Report

Page (3/5)



CCalc 2.6
Copyright © 2023, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, October 12, 2023
Tester	Simon Blohm
Display	ASUS VA34VCPSN
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	63 255 127	13.11	7.75	0.79	4.37
	63 255 191	12.23	4.44	0.71	3.97
	63 255 255	11.21	2.38	0.56	3.91
	127 0 0	5.04	3.49	0.38	2.30
	127 0 63	6.76	0.53	0.04	2.08
	127 0 127	6.14	2.87	0.11	2.06
	127 0 191	5.16	3.69	0.20	1.80
	127 0 255	2.83	3.44	0.39	1.33
	127 63 0	4.40	3.91	0.61	2.67
	127 63 63	4.78	2.24	0.27	2.55
	127 63 127	5.59	1.67	0.48	2.16
	127 63 191	4.33	2.91	0.66	1.79
	127 63 255	1.78	2.71	0.86	1.38
	127 127 0	3.82	0.72	0.30	1.17
	127 127 63	1.60	1.24	0.55	1.16
	127 127 127	1.02	0.20	0.74	1.27
	127 127 191	0.54	0.34	0.81	0.87
	127 127 255	1.19	0.49	1.06	1.12
	127 191 0	9.03	4.16	0.42	2.69
	127 191 63	6.94	4.57	0.22	2.81
	127 191 127	5.01	3.99	0.31	3.01
	127 191 191	5.00	0.71	0.50	2.66
	127 191 255	0.23	5.02	0.71	3.28
	127 255 0	14.15	5.13	1.05	3.25
	127 255 63	11.41	5.79	0.69	3.18
	127 255 127	8.28	6.28	0.59	3.47
	127 255 191	7.80	4.09	0.52	3.26
	127 255 255	7.61	1.72	0.38	3.08
	191 0 0	10.67	2.01	0.09	2.40
	191 0 63	9.94	1.19	0.33	2.50
	191 0 127	9.67	1.76	0.36	2.44
	191 0 191	8.29	4.31	0.44	2.45
	191 0 255	5.39	5.21	0.57	2.13
	191 63 0	10.32	3.15	0.01	2.79
	191 63 63	8.11	3.17	0.58	2.85
	191 63 127	8.77	0.11	0.73	2.56
	191 63 191	7.41	3.43	0.82	2.42
	191 63 255	4.35	4.66	0.99	2.19
	191 127 0	6.54	2.43	0.13	2.04
	191 127 63	3.35	2.24	0.83	1.87
	191 127 127	3.45	1.79	1.03	2.27
	191 127 191	3.45	1.71	1.12	1.94
	191 127 255	0.76	2.58	1.31	1.81
	191 191 0	6.88	0.19	0.09	1.53
	191 191 63	3.69	0.90	0.48	1.17
	191 191 127	0.30	0.97	0.62	0.90
	191 191 191	0.67	0.19	0.72	1.00

Colorimetric Report

Page (4/5)



CCalc 2.6
Copyright © 2023, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, October 12, 2023
Tester	Simon Blohm
Display	ASUS VA34VCPSN
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E94
	191 191 255	1.15	0.56	0.90	1.07
	191 255 0	10.49	1.63	0.86	2.18
	191 255 63	7.32	2.58	0.50	1.87
	191 255 127	3.24	3.52	0.39	1.96
	191 255 191	2.59	3.03	0.32	2.13
	191 255 255	3.54	0.95	0.15	1.97
	255 0 0	16.90	1.02	0.17	2.99
	255 0 63	12.67	2.31	0.27	2.68
	255 0 127	12.40	0.82	0.32	2.62
	255 0 191	11.67	2.93	0.34	2.54
	255 0 255	8.91	5.52	0.46	2.52
	255 63 0	15.52	0.58	0.19	2.89
	255 63 63	10.52	3.54	0.60	2.77
	255 63 127	10.79	2.31	0.67	2.78
	255 63 191	10.47	1.85	0.78	2.46
	255 63 255	7.48	4.86	0.93	2.47
	255 127 0	11.60	1.82	0.35	2.54
	255 127 63	6.96	2.92	0.88	2.35
	255 127 127	6.14	2.86	1.05	2.61
	255 127 191	6.61	0.77	1.12	2.21
	255 127 255	4.04	3.73	1.26	2.31
	255 191 0	9.29	1.61	0.12	2.08
	255 191 63	4.92	1.62	0.56	1.53
	255 191 127	1.35	2.48	0.74	1.73
	255 191 191	2.63	1.39	0.84	1.82
	255 191 255	1.25	1.90	1.00	1.62
	255 255 0	10.22	1.12	0.64	2.06
	255 255 63	5.89	0.41	0.36	1.26
	255 255 127	0.73	0.06	0.31	0.36
	255 255 191	0.95	0.02	0.19	0.43
	255 255 255 (1)	-	-	-	-
	Average (2)	6.50	2.86	0.58	2.42
	Maximum (2)	19.08	8.20	2.19	4.88

(1) Visual adaptation to display whitepoint is assumed; CIELAB reference values are adapted (Bradford transformation) to display whitepoint
(2) Without Black

Color Space	Gamut Volume CIELAB D50
sRGB	98%

Colorimetric Report

Page (5/5)



CCalc 2.6
Copyright © 2023, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Thursday, October 12, 2023
Tester	Simon Blohm
Display	ASUS VA34VCPSN
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	sRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

Property	Device adjustments
Backlight brightness	
Brightness	
Contrast	
RGB Gain	
Gradation	
Other	Alle Werte sind im sRGB-Modus gesperrt und auch nicht einsehbar!