

Colorimetric Report

Page (1/1)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Tuesday, November 19, 2024
Tester	
Display	
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6125 Kelvin
White Point XYZ (normalized)	95.43 100.00 103.40
DeltaE to D50/ D65	15.71/ 3.48
Assumed Target Whitepoint (1)	6100 Kelvin
DeltaE to Assumed Target Whitepoint	0.76
Brightness	181.12 cd/m²
Black Point	0.00 cd/m²
Contrast (x:1)	-
Gradation (Average)	2.25

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6193	0.15	-	2.30
	15	5964	0.36	-	2.30
	20	5844	0.79	-	2.29
	25	5839	1.02	-	2.25
	30	5908	0.83	-	2.26
	35	5937	0.81	-	2.24
	40	5995	0.60	-	2.24
	45	5966	0.83	-	2.23
	50	5979	0.83	-	2.23
	55	5993	0.80	-	2.23
	60	6018	0.70	-	2.21
	65	6051	0.50	-	2.23
	70	6078	0.32	-	2.25
	75	6123	0.04	-	2.24
	80	6109	0.15	-	2.23
	85	6102	0.20	-	2.25
	90	6113	0.10	-	2.21
	95	6117	0.15	-	2.22
	100 (2)	6124	-	-	-
	Average (3)	-	0.53	-	2.25
	Maximum (3)	-	1.02	-	-
	Range (3)	-	1.03	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

