

Colorimetric Report

Page (1/1)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Tuesday, May 6, 2025
Tester	Simon Blohm
Display	EIZO EV2410R
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6304 Kelvin
White Point XYZ (normalized)	94.29 100.00 104.33
DeltaE to D50/ D65	16.68/ 3.13
Assumed Target Whitepoint (1)	6300 Kelvin
DeltaE to Assumed Target Whitepoint	1.63
Brightness	219.73 cd/m²
Black Point	0.18 cd/m²
Contrast (x:1)	1221:1
Gradation (Average)	2.15

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6698	0.68	-	2.14
	15	6520	0.56	-	2.17
	20	6379	0.22	-	2.17
	25	6354	0.25	-	2.17
	30	6349	0.17	-	2.17
	35	6344	0.17	-	2.17
	40	6339	0.26	-	2.17
	45	6332	0.27	-	2.17
	50	6338	0.20	-	2.16
	55	6292	0.14	-	2.15
	60	6311	0.15	-	2.15
	65	6306	0.13	-	2.14
	70	6304	0.04	-	2.14
	75	6328	0.18	-	2.14
	80	6302	0.02	-	2.13
	85	6312	0.09	-	2.12
	90	6294	0.09	-	2.11
	95	6295	0.11	-	2.11
	100 (2)	6304	-	-	-
	Average (3)	-	0.18	-	2.15
	Maximum (3)	-	0.56	-	-
	Range (3)	-	0.69	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

