

Colorimetric Report

Page (1/5)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, October 18, 2025
Tester	Simon Blohm
Display	LG 32U9990A
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	AdobeRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel


White Point (CCT)	6689 Kelvin
White Point XYZ (normalized)	90.23 100.00 103.29
DeltaE to D50/ D65	19.00/ 9.27
Assumed Target Whitepoint (2)	6700 Kelvin
DeltaE to Assumed Target Whitepoint	9.92
Brightness	190.72 cd/m²
Black Point	0.11 cd/m²
Contrast (x:1)	1734:1
Gradation (Average)	2.16

(2) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6766	0.61	1.62	2.10
	15	6683	0.35	1.48	2.12
	20	6639	0.49	1.24	2.14
	25	6630	0.67	0.91	2.17
	30	6629	0.63	0.81	2.17
	35	6660	0.81	0.96	2.17
	40	6688	0.56	0.70	2.18
	45	6669	0.44	0.63	2.17
	50	6695	0.23	0.42	2.18
	55	6662	0.41	0.57	2.17
	60	6644	0.59	0.73	2.17
	65	6688	0.40	0.56	2.17
	70	6691	0.01	0.42	2.16
	75	6665	0.57	0.67	2.16
	80	6662	0.39	0.58	2.14
	85	6631	0.54	0.73	2.11
	90	6665	0.92	0.98	2.10
	95	6687	1.08	1.08	2.24
	100 (3)	6690	-	-	-
	Average (4)	-	0.53	0.8	2.16
	Maximum (4)	-	1.08	1.48	-
	Range (4)	-	1.08	-	-

(3) Visual adaptation to display whitepoint is assumed
(4) Only luminance > 1% considered

Corresponding Gamma



Colorimetric Report

Page (2/5)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, October 18, 2025
Tester	Simon Blohm
Display	LG 32U9990A
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	AdobeRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E00
	0 0 0	0.42	0.00	0.54	0.54
	0 0 63	0.68	0.90	0.83	0.82
	0 0 127	3.74	1.67	1.59	1.53
	0 0 191	4.58	2.19	1.86	1.82
	0 0 255	6.47	2.82	2.09	2.22
	0 63 0	3.63	2.11	0.55	1.48
	0 63 63	2.55	1.09	0.64	1.49
	0 63 127	0.02	1.76	0.67	1.44
	0 63 191	0.32	1.15	0.63	0.89
	0 63 255	0.22	0.90	0.41	0.62
	0 127 0	7.53	5.42	0.59	2.37
	0 127 63	8.23	2.70	0.63	2.28
	0 127 127	6.06	1.69	0.59	2.30
	0 127 191	1.36	4.41	0.58	2.60
	0 127 255	0.03	3.20	0.48	2.17
	0 191 0	10.90	6.09	0.68	2.38
	0 191 63	10.62	5.20	0.69	2.41
	0 191 127	10.10	2.19	0.70	2.34
	0 191 191	7.98	2.26	0.62	2.48
	0 191 255	3.99	4.68	0.56	2.40
	0 255 0	14.61	7.96	0.20	2.59
	0 255 63	14.58	7.14	0.21	2.60
	0 255 127	14.07	4.37	0.20	2.52
	0 255 191	12.94	0.64	0.26	2.45
	0 255 255	9.94	2.76	0.21	2.61
	63 0 0	1.21	2.02	0.51	1.52
	63 0 63	0.05	0.69	0.30	0.42
	63 0 127	0.37	0.09	0.13	0.14
	63 0 191	1.86	1.03	0.87	0.86
	63 0 255	4.53	1.96	1.38	1.52
	63 63 0	0.99	0.75	0.52	0.75
	63 63 63	0.60	0.13	0.63	1.00
	63 63 127	0.02	0.33	0.52	0.48
	63 63 191	0.24	0.39	0.51	0.48
	63 63 255	0.51	0.34	0.40	0.42
	63 127 0	3.71	3.59	0.53	1.68
	63 127 63	4.78	2.26	0.58	1.77
	63 127 127	3.97	1.12	0.56	1.90
	63 127 191	0.43	3.29	0.51	2.19
	63 127 255	0.01	2.23	0.45	1.60
	63 191 0	8.20	5.27	0.67	2.08
	63 191 63	8.33	4.46	0.61	2.10
	63 191 127	8.31	2.04	0.62	2.14
	63 191 191	6.74	2.02	0.61	2.33
	63 191 255	3.24	4.16	0.55	2.25
	63 255 0	12.27	7.27	0.28	2.36
	63 255 63	12.38	6.53	0.24	2.38

Colorimetric Report

Page (3/5)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, October 18, 2025
Tester	Simon Blohm
Display	LG 32U9990A
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	AdobeRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E00
	63 255 127	12.59	4.24	0.20	2.41
	63 255 191	11.81	0.73	0.21	2.36
	63 255 255	9.40	2.57	0.23	2.59
	127 0 0	2.81	3.28	0.25	2.04
	127 0 63	3.89	0.58	0.29	1.19
	127 0 127	2.38	1.45	0.17	0.85
	127 0 191	1.04	1.41	0.12	0.62
	127 0 255	0.13	0.58	0.17	0.28
	127 63 0	1.87	2.13	0.18	1.47
	127 63 63	2.39	0.98	0.21	1.11
	127 63 127	1.57	1.06	0.17	0.74
	127 63 191	0.53	1.08	0.16	0.55
	127 63 255	0.78	0.63	0.11	0.32
	127 127 0	0.45	0.17	0.38	0.40
	127 127 63	0.36	0.21	0.40	0.44
	127 127 127	0.27	0.12	0.37	0.53
	127 127 191	0.33	0.34	0.35	0.41
	127 127 255	0.27	0.41	0.29	0.41
	127 191 0	3.08	3.02	0.54	1.31
	127 191 63	2.82	2.55	0.52	1.23
	127 191 127	3.35	1.74	0.54	1.39
	127 191 191	3.58	1.32	0.50	1.85
	127 191 255	1.31	2.69	0.45	1.89
	127 255 0	7.46	5.55	0.14	1.86
	127 255 63	7.84	5.44	0.13	1.98
	127 255 127	8.22	3.72	0.12	1.99
	127 255 191	8.21	1.07	0.18	2.03
	127 255 255	7.06	2.16	0.13	2.41
	191 0 0	2.67	4.14	0.10	2.15
	191 0 63	4.11	2.13	0.07	1.39
	191 0 127	4.25	0.68	0.09	1.00
	191 0 191	2.83	2.07	0.08	0.91
	191 0 255	2.42	1.89	0.09	0.76
	191 63 0	2.17	3.80	0.02	2.09
	191 63 63	3.55	2.42	0.06	1.58
	191 63 127	3.65	0.46	0.03	0.96
	191 63 191	2.37	1.85	0.02	0.87
	191 63 255	2.11	1.69	0.11	0.73
	191 127 0	0.61	2.80	0.20	1.69
	191 127 63	0.90	2.33	0.19	1.57
	191 127 127	2.18	0.80	0.17	1.04
	191 127 191	1.31	1.20	0.10	0.76
	191 127 255	1.18	0.80	0.10	0.48
	191 191 0	0.13	0.20	0.37	0.29
	191 191 63	0.03	0.05	0.32	0.23
	191 191 127	0.18	0.16	0.33	0.27
	191 191 191	0.53	0.18	0.36	0.84

Colorimetric Report

Page (4/5)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, October 18, 2025
Tester	Simon Blohm
Display	LG 32U9990A
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	AdobeRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

	RGB	Delta C	Delta H	Delta L	Delta E00
	191 191 255	0.49	0.48	0.33	0.58
	191 255 0	2.97	3.49	0.17	1.31
	191 255 63	2.93	3.43	0.18	1.35
	191 255 127	3.45	3.00	0.19	1.46
	191 255 191	4.42	1.58	0.06	1.66
	191 255 255	3.87	1.36	0.09	2.03
	255 0 0	3.57	5.55	0.61	2.63
	255 0 63	5.04	3.66	0.60	1.95
	255 0 127	5.90	0.25	0.61	1.27
	255 0 191	4.86	2.24	0.57	1.24
	255 0 255	3.99	2.66	0.62	1.14
	255 63 0	3.20	5.50	0.53	2.68
	255 63 63	4.64	3.89	0.52	2.10
	255 63 127	5.75	0.71	0.52	1.31
	255 63 191	4.92	1.98	0.48	1.25
	255 63 255	4.02	2.52	0.54	1.14
	255 127 0	2.17	5.32	0.25	2.81
	255 127 63	3.19	4.67	0.24	2.66
	255 127 127	4.77	2.26	0.21	1.76
	255 127 191	4.50	1.19	0.25	1.29
	255 127 255	3.75	2.17	0.20	1.17
	255 191 0	0.29	3.74	0.01	2.05
	255 191 63	0.59	3.85	0.01	2.27
	255 191 127	1.69	3.37	0.01	2.38
	255 191 191	2.92	0.66	0.00	1.34
	255 191 255	2.55	1.34	0.04	1.14
	255 255 0	0.01	0.85	0.13	0.39
	255 255 63	0.00	0.58	0.12	0.29
	255 255 127	0.13	0.61	0.11	0.35
	255 255 191	0.60	0.11	0.03	0.25
	255 255 255 (1)	-	-	-	-
	Average (2)	3.81	0.00	0.38	1.49
	Maximum (2)	14.61	7.96	2.09	2.81

(1) Visual adaptation to display whitepoint is assumed; CIELAB reference values are adapted (Bradford transformation) to display whitepoint
(2) Without Black

Color Space	Gamut Volume CIELAB D50
AdobeRGB	88%

Colorimetric Report

Page (5/5)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Saturday, October 18, 2025
Tester	Simon Blohm
Display	LG 32U9990A
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	In accordance with ISO 12646:2007 (1)
Target	AdobeRGB
Display Profile	Not considered
Rendering Intent	-

(1) Five equally spaced code values for each channel

Property	Device adjustments
Backlight brightness	
Brightness	40
Contrast	70
RGB Gain	50 50 50
Gradation	Modus 2
Other	