

Colorimetric Report

Page (1/1)



CCalc 2.7
Copyright © 2024, Denis Freund
All Rights Reserved
lic. for PRAD ProAdviser

Date	Friday, November 14, 2025
Tester	Manuel Findeis
Display	EIZO CG3100X
Sensor	X-Rite i1 Display Pro (Corr.: Generic)
Testchart	Only neutral colours
Target	Greybalance
Display Profile	Not considered
Rendering Intent	-

White Point (CCT)	6464 Kelvin
White Point XYZ (normalized)	94.64 100.00 107.56
DeltaE to D50/ D65	18.73/ 1.08
Assumed Target Whitepoint (1)	6500 Kelvin
DeltaE to Assumed Target Whitepoint	0.99
Brightness	99.90 cd/m ²
Black Point	0.06 cd/m ²
Contrast (x:1)	1665:1
Gradation (Average)	2.21

(1) Daylight

	Percent	Kelvin	Delta C	Delta E	Gamma
	5	-	-	-	-
	10	6609	0.21	-	2.17
	15	6525	0.13	-	2.19
	20	6522	0.16	-	2.20
	25	6506	0.14	-	2.20
	30	6493	0.11	-	2.21
	35	6489	0.18	-	2.21
	40	6462	0.31	-	2.21
	45	6472	0.28	-	2.22
	50	6472	0.20	-	2.22
	55	6475	0.10	-	2.21
	60	6456	0.30	-	2.22
	65	6455	0.37	-	2.22
	70	6454	0.22	-	2.22
	75	6451	0.40	-	2.22
	80	6445	0.35	-	2.22
	85	6466	0.22	-	2.20
	90	6462	0.19	-	2.20
	95	6463	0.22	-	2.22
	100 (2)	6464	-	-	-
	Average (3)	-	0.23	-	2.21
	Maximum (3)	-	0.4	-	-
	Range (3)	-	0.45	-	-

(2) Visual adaptation to display whitepoint is assumed
(3) Only luminance > 1% considered

Corresponding Gamma

